

Airbus Defence and Space

Signature technology group

Influences of wind farms on modern ASR Radarsystems with consideration of multi-level doppler filter procedures

(The possibilities for the reduction of WT effects on digital atc radars
-Results from own projects and several current measurements-)

Dr.-Ing. A. Frye, Labor für Signaturtechnik
**öffentlich bestellter und vereidigter Sachverständiger für
Hochfrequenz- und Signaturtechnik**

November 2017
Tel. +049-421-538 -2719
E-Mail: andreas.frye@airbus.com

Airbus Defence and Space GmbH
Abt. Signaturtechnik, Dr. A. Frye
Airbusallee 1
28199 Bremen

AIRBUS

Presentation:

- 1. Open questions for the WT- influence on digital ATC-
radars**

- 2. The technical possibilities we have today**
 - a. at the radar ?**
 - b. at the WT / at the wind farm ?**

- 3. Results / Overview**

1. Open questions for the WT- influence on digital ATC - Radars

WTs (Wind Turbines) will reduce the detection of overflying aircrafts for modern civil and military multi level doppler filter ATC -Radars

- How strong is the influence of the Windfarm –Layout or Windfarm-Size ?
- How strong is the influence of the Aircraft path ?
- How strong is the influence of the wind direction ?
- How good is a „switch-of“- possibility for the ATC ?
- Can we realise a „direction control“ at the WT ?
- How good is the influence of „low reflection“ rotorblades ?
- Can we combine some of these options ?

2. The technical possibilities do we have today

a. at the radar ?

b. at the WT / at the wind farm ?

At the radar:

- * Remote switch-of possibility for severals Wind turbines**
- * Remote switch-of possibility for a complete Windfarm**


At the WT :

- * Direction control of the WT / No directions with strong reflections are given**
- * use of the direction charakteristics of the WT**
- * take the main wind direction into account**
- * use of low reflecting rotorblades**

Introduction



Many data recordings / many measurement at modern radars are made in the last few years

Example windfarm:
4 Wind turbines in a row



Large distance from the atc- radar





The DCM-Map will be updated ongoing and indicates a average level for each cell.

Ground-Clutter Map (fading out of fixed targets):

The cells show, where an „influence“ by the WEA will be possible.

Digital-Clutter Map (Fading out of moving targets : WTs, traffic, etc.):

The colour of the cells show, where a **smart / middle/ strong influence** from the Wind turbines on the detection on overflying aircraft can be expected


2. The technical possibilities we have today a. at the Radar ?

- Direction control of the WT / No directions with strong reflections are given
- take the main wind direction into account
- use of low reflecting rotorblades

Typical Reflection characteristic of a wind turbine and Pd of an overflight aircraft:

Rotoraxis direction vs. reflexion characteristics (RQS_{dyn} vs. direction)

Data basic: analysis of the signal processing unit of an radar manufacturer with an 8-step doppler-filter algorithm



At 180° : Rotoraxis is orientated to the radar (here we don't have an aircraft loss)
Chance of the aircraft-detection => 100%)


At 120° : Low Influence on the overflight aircraft detection rate => 95% (Winddirection 2)

At 10° : Clear influence on the overflight aircraft detection rate => 45% (Winddirection 1)


At 20° : Strong influence on the overflight aircraft detection rate => 67% (Winddirection 1a)

2. The technical possibilities do we have today ? a. at the radar ?

All wind turbines are orientated in the main wind direction; here 180° to the radar



wind direction distribution
Windrichtung Verteilung in (%)
Jahr



For the main wind direction all cells are green


=> not or very low influence
for flightpath A or B

2. The technical possibilities do we have today ?

a. at the radar ?

Situation:


all WT operating
Winddirection 1




Flight path A
Detection loss rate:
8 detections with ca. 95%

Flight path B
Detection loss rate:
3 detections with ca. 90%

A



B




2. The technical possibilities we have today

a. at the radar ?

Situation:


all WT operating
 Winddirection 1a




Flight path A
 aircraft track loss for
 7 Detektions with ca.93%

Flight path B
 aircraft track loss for
 3 Detektions with ca.60%

A



B




2. The technical possibilities we have today

a. at the radar ?

Situation:


all WT operating
Winddirection 2




Flight path A
No aircraft track loss

Flight path B
No aircraft track loss

A




B



2. The technical possibilities we have today

a. at the radar ?


Situation: **WT 2 und 3 not in operation by remote
 Winddirection 1**




Flight path A
 aircraft track loss for
 5 Detektions with ca.55%

Flight path B
 aircraft track loss for
 3 Detektions with ca.88%

A




B



2. The technical possibilities we have today a. at the radar ?


Situation: **WT 2 and 3 not in operation**
 (by remote)
 Winddirectiong 2




Flight path A
No aircraft track loss

Flight path B
No aircraft track loss

A




B



2. The technical possibilities we have today b. at the WT ?

Low reflecting blades of a wind turbine: **Rotoraxis direction vs. RCS (RQS_{dyn} vs. direction)**



Rotoraxis is orientated to the radar
 (here we don't have an aircraft loss)
 Chance of the aircraft-detection
 => 100%)

At 120° : Low Influence on the overflight
 a/c detection rate => 96%
 (Winddirection 2)


At 10° : Clear influence on the overflight
 a/c detection rate => 82%
 (Winddirection 1)

At 20° : Strong influence on the overflight
 a/c detection rate => 89%
 (Winddirection 1a)

2. The technical possibilities we have today



b. at the WT ?

Situation: **all WT operating**
low reflecting blades
Winddirection 1



Flight path A
No aircraft track loss
(under 30%)


Flight path B
No aircraft track loss
(unter 20%)



2. The technical possibilities we have today



b. at the WT ?

Situation: **all WT operating**
low reflecting Blades
Winddirections 1a and 2



Flight path A
No aircraft track loss

Flight path B
No aircraft track loss



3. Summary

Option:	Flightpath A	Flightpath B
All WT operating (Winndirection 1) (Winndirection1a) (Winndirection 2)	8 Detectionen with 95%(40 sek.) 7 Detektionen with 93% (35 sek.) track loss	5 Detektionen with 90% (25 sek.) 3 Detektionen with 60% (15 sek.) track loss
Wt 2 +3 remote Switch off (Winndirection 1) (Winndirection 2)	5 Detections with 55%(25sek.) track loss	3 Detections with 88% (15sek.) track loss
All WT operating (Low reflecting blades) (Winndirection 1) (Winndirection 2)	6 Detections with 30% no track loss	4 Detections under 30% no track loss
All WT operating (no critical WT orientations & low reflecting blades) (Winndirection 1a) (Winndirection 2)	All Wind directions: Detections under 30% = no track loss	All Wind directions: Detections under 10% = no track loss

Danke für Ihre Aufmerksamkeit

Thank you for your attention